

PRODUCT DATASHEET



PAROC Comfort Tape W

PAROC Comfort Tape White is a white tissue tape with a modified acrylic adhesive with siliconized liner.

It is used for sealing the joints when using PAROC Comfort and N1 faced products. PAROC Comfort Tape W gives a great finish, safe installation and usage.

DIMENSIONS	
Width	50, 75 and 110 mm
Length	50 m
Volume	Rolls / carton: 50mm / 24 pcs, 75mm / 18 pcs, 110mm / 12 pcs.
Cartons / pallet 24 pcs.	

Appearance

Facing Material	Background: Polypropylene tissue 30 g/m ² ± 5%
COLOURS	
White	

Handling

INSTALLATION	
During the installation, the insulation material to be taped should be at a minimum temperature of +5 Celsius. Allow the temperature of the insulating material to adjust to the ambient installation temperature. Make sure that the surfaces to be joined with tape are clean, dry free of dust and grease. Surface must be free from oil, fat, dust and solvents before film/tape application. Do not use cleaners containing anti-adhesive agents. Some plastics and paints may discharge anti-adhesive agents leading to bonding failure. Rough and uneven surfaces may weaken bonding. Installation temperature: +5°C - +30°C	
Storage	Product should be stored in original packaging, laid flat on the slit edge of the roll. Storage in dry and clean areas, at normal temperature, protected from direct sunlight and heat sources. Storage conditions: -10°C - +30°C, under dry conditions inside a warehouse

We strongly advise users to test the product's suitability for their own particular requirement. All data and recommendations contained in this Technical Data Sheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate tape for a given application. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Our sales team is also available to assist customers with their tape.

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, www.paroc.com

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application or the installation of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material. As a result of constant further development of our products we reserve the right to make alterations to our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries: international use (general information).