

PRODUCT DATASHEET



PAROC XSS 015

Capillary break

Extruded polyethylene strip with longitudinal grooves on the underside and the top covered with a protruding LD polyethylene film.

Capillary break seal between the sill and foundation fitted with air and vapor tight overlap, which also provides protection for the sill during construction.

Approval (Ground plate seal): P-marked (2082/96); Approval (Plastic): P-marked (0278/08), CE-marked (EN 13984)

Package Type Plastic sack

DIMENSIONS	
Thickness	5/8 mm
Width	200, 240, 260, 280 mm. Plastic overlap: 320-360 mm
Length	40 m

Properties

PROPERTY	VALUE	ACCORDING TO
FIRE PROPERTIES		
Combustibility	Combustible	EN ISO 1182

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, www.paroc.com

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application or the installation of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material. As a result of constant further development of our products we reserve the right to make alterations to our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries: international use (general information).