

## PRODUCT DATASHEET



## **PAROC Head Pin Insulated**

PAROC Head Pin Insulated is designed for capacitor discharge welding devices for welding directly through the insulation.

The PAROC Head Pin Insulated fasteners allow the fixing in a single operation of aluminum faced insulation such as lamella mats or wired mats on metal surfaces (ventilation ducts, metal beams, metal industrial, ventilation or air condition equipment, etc.).

Material: Cup: galvanized. Pin: standard – coppered (galvanized, stainless steel).

Package Type

Delivered in plastic buckets: 500 (standard) or 1000 pcs.



## **Properties**

PROPERTY	VALUE	ACCORDING TO
OTHER PROPERTIES		
Cup diameter Pin diameter Length (Cup + Pin) Material Overlay	30 mm 2,7 mm 19-245 mm St37 / 1.4301 Cu / Zn	

## Handling

INSTALLATION		
	Make sure that the surfaces to be welded are clean, dry, free of dust and grease. Surface must be free from oil, fat, dust and solvents before pin application.	

Depending on the final effect you may use two different length of the pins: 1. Quilted surface - for the products up to 50 kg/m³ use the pins with the length little bit smaller than nominal insulation thickness (example: for insulation thickness 30 mm use 28,5 mm pin). 2. Flat surface – for all densities use the pins with the length little bit higher than nominal insulation thickness (example: for insulation thickness 30 mm use 30,5 mm pin).

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, www.paroc.com

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application or the installation of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material. As a result of constant further development of our products we reserve the right to make alterations to our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries international use (general information).