

PAROC PRO SLAB REFERENCE TABLE

NEW PRODUCTS WITH IMPROVED FEATURES

NOMINAL DENSITY



MAXIMUM SERVICE TEMPERATURE

NOMINAL DENSITY	PRODUCT	MAXIMUM SERVICE TEMPERATURE (°C)
40	PAROC PRO SLAB 350 WR	350
40	PAROC PRO SLAB 350 ALUCOAT	350
40	PAROC PRO SLAB 350 ALUCOAT WR	350
40	(PAROC PRO SLAB 40)*	350
60	PAROC PRO SLAB 450 WR	450
60	PAROC PRO SLAB 450 ALUCOAT	450
60	PAROC PRO SLAB 450 ALUCOAT WR	450
60	(PAROC PRO SLAB 60)*	350
80	PAROC PRO SLAB 640 WR	640
80	PAROC PRO SLAB 640 ALUCOAT	640
80	PAROC PRO SLAB 640 ALUCOAT WR	640
80	(PAROC PRO SLAB 80)*	550
100	PAROC PRO SLAB 660 WR	660
100	PAROC PRO SLAB 660 ALUCOAT	660
100	PAROC PRO SLAB 660 ALUCOAT WR	660
100	(PAROC PRO SLAB 100)*	640
120	PAROC PRO SLAB 680 WR	680
120	PAROC PRO SLAB 680 ALUCOAT	680
120	PAROC PRO SLAB 680 ALUCOAT WR	680
120	(PAROC PRO SLAB 120)*	640
150	PAROC PRO SLAB 700 WR	700
150	PAROC PRO SLAB 700 ALUCOAT	700
150	PAROC PRO SLAB 700 ALUCOAT WR	700
150	(PAROC PRO SLAB 150)*	640

NEW PRODUCTS WITH IMPROVED FEATURES:

■ WATER-REPELLENT
 ■ ALUMINIUM FACING
 ■ ALUMINIUM FACING WITH WATER REPELLENCY
 ■ *(PREVIOUS PRODUCTS)